

## INI-TS-IG2000-ICMF-A IntelliGEN™ 2000 AUTO Flex-Fuel Generator

(Made in the USA, U.S. Patent 9,175,601, U.S. Patent 9,188,033, and other U.S. and foreign patents pending)



### Features

- Autostart capable with optional ALLY™
- Can use multiple fuel types (JP-8/F-24, F-34 “NATO”, gasoline, propane, methanol, isopropanol)
- Lightweight, “One Man Portable”
- Quiet, small noise signature
- Plug-in compatible with Trinity™ Systems or stand-alone
- Immediate functionality on startup – No waiting
- Auto turn down when load is low
- 2,000 hour rated lifetime low maintenance
- 2,000 hour/2 year limited warranty (repair or replace)

### INI-TS-IG2000-ICMF-A Includes

- 1 x IntelliGEN™ 2000 Auto Flex Fuel Generator v3.5 (p/n INI-TS-IG2000-ICMF-A)
- 1 x Initial Oil Fill Bottle
- 1 x 12.5' Extended Exhaust Piping w/ Clamp
- 1 x Parallel "Y" Cable w/ Adapter
- 1 x Field Level 2kW Maintenance Kit
- 1 x Operator Manual
- 2 x Cold Start Canister (Removed for air shipment)
- 2 x Quart 10W40 Small Engine Oil
- 1 x Quick Reference Card
- 1 x Autostart Motor Assy w/ Comms Cable (p/n 10097)
- 1 x Battery Start Cable (p/n 10139)

### Specs

- Start System: AUTO or Manual Recoil Start
- Max Peak Output: 2000W (Sea Level) (Gasoline and JP-8/F-24)
- Gasoline Nominal Output: 1600W (Sea Level)
- Gasoline Nominal Voltage: 110-240VAC, 50 or 60Hz
- JP-8/F-24 Nominal Output: 1250W (Sea Level)
- JP-8/F-24 Nominal Voltage: 110-240VAC, 50 or 60Hz
- Dry Weight: 44.7 lb. (20 kg)
- Dimensions: 20.5" x 14.5" x 17.9" (521 mm x 369 mm x 455 mm)
- Operating Temp: -4°F to 122°F (-20°C to 50°C) (In Manual Mode)
- Operating Temp: 32°F to 104°F (0°C to 40°C) (In AUTO Mode)
- Storage temp: -40°F to 176°F (-40°C to 80°C)
- Operating Elevation: Sea Level to 10,000 ft. (3048 m)
- AC Output Power outlets: Customer Specified
- Internal Tank: 1.1 gal (4.1 L), Quick connect for compressed fuels
- Color: CARC Tan or Green

